

APPLICATIONS	Food, pharmaceutical, chemical applications	
MAX. FLOWRATE	15 m³/h (with water)	
MAX. NUMBER OF PLATES	73	
FRAME	PN6, PN10 (standard PN6) on request PN16	
MATERIALS	FRAME	Stainless steel AISI 304 – AISI 316
	PLATES	Stainless steel AISI 304 – AISI 316 titanium, incoloy, monel, hastelloy
	GASKETS	NBR, EPDM, EPM, FKM, Silicone
	CONNECTIONS	Stainless steel, Polypropylene, PTFE (Teflon)

DIMENSIONS		
NOMINAL PRESSURE	PN6	PN10
A	204	210
B	86	86
C	540	540
D	381	381
F	N° of plates x 2,65	N° of plates x 2,65
G	DN32	DN32
H	104,5	104,5
S1 / S2	15 / 12	18 / 15
unit. surface (m²)	0,048	0,048
Channel Vol. (l)	0,102	0,102
Plate weight (Kg)	0,29	0,29
Plate thickness (mm)	0,5	0,5
Frame weight (Kg)	27	35
Boltings	N°8 M12	N°8 M14

N° OF PLATES	13	25	37	49	61
E	265	315	365	415	465

DIMENSIONS

